

LVT COLLECTION

 **REPUBLIC**



BIGGER 5

AN URBAN JUNGLE ADVENTURE



	Characteristics	Standards	Grizzly / Crocodile
Floor Properties	Total Thickness	EN ISO 24346	2.5mm
	Wear Layer	EN ISO 24340	0.55mm
	Finish		UV COATING
	Surface		Registered Embossing (EIR)
	Installation Method		Gluedown
	Usage Class	EN 15468	Residential / Commercial
Packing Properties	Planks Size (L*W)		1219*228mm
	Pallet Size (W*L*H)		1000*1250*720mm
	Planks/package (sqm/package)		16 (4.44 sqm)
	Weight/package		21.66kg
	Package/pallet		52
	sqm/pallet		230.8 sqm
	sqm/container		4617 sqm
	Pallet/container		20
	Package/container		1040
Behaviour to Heat	Total weight/pallet		1146kg
	Behaviour to Fire	EN 13501-1	Bfi-S1
	Underfloor Heating Suitability		-30°C to +70°C
Technical Properties	Static Electrical Propensity	EN 14041	0.5kV, Pass
	Slip Resistance	EN 13893	DS/R9
	Residual Indentation	EN ISO 24343-1	≤ 1%
	Dimensional Stability	EN ISO 23999	≤ 0.15%
Toxic Substances	Formaldehyde / VOC Emission	EN 717-1	E1 / VOC Free
	Greenguard		Pass
	Phthalate Free		Yes



DryBack

• MAXimum strength • MAXimum durability • MAXimum stability • MAXimum style